



# DIRECTIONAL LIGHTS DL-20-MR16-SERIES



TYPE

## SPECIFICATIONS

**CONSTRUCTION:** Cast aluminum, cast brass or composite Bullet; matching heavy duty cast aluminum, brass or composite adjustable swivel; matching extension collar with lens

**LENS:** High impact clear tempered convex glass

**O-RING:** High temperature red silicone

**LAMP SUPPLIED:** 75 watt MR16 FL(EYC) 5000 hours average rating (75w max)

**LAMP OPTIONS:** We recommend 20 watt MR16 ULTRA10, 000 hours average rating; 20 watt MR16 TITAN 18, 000 hours average rating; 4w ARROW LED 50,000 average rating

**SOCKET:** High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

**WIRING:** Black 3 foot 18/2 zip cord from base of fixture (12v. only)

For 25 foot 16/2 fixture lead wire add **-25F** to catalog number.

**CONNECTION:** FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

**MOUNTING:** FA-03 black 9" ABS stake threaded 1/2" NPS

**FINISH:** Aluminum-Black texture polyester powder coat; optional finishes available  
Brass-Unfinished brass; optional finishes available



## ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-20-MR16-BLT	Cast aluminum Bullet	75w MR16 FL(EYC)	2.0 lbs.
DL-20-MR16-BRS	Cast brass Bullet	75w MR16 FL(EYC)	3.0 lbs.
CDL-20-MR16-BLT	Composite Bullet	75w MR16 FL(EYC)	2.0 lbs.
DL-20-AC-MR16-BLT	Cast aluminum Bullet, angle collar	75w MR16 FL(EYC)	3.0 lbs.
DL-20-AC-MR16-BRS	Cast brass Bullet, angle collar	75w MR16 FL(EYC)	5.0 lbs.
CDL-20-AC-MR16-BLT	Composite Bullet, angle collar	75w MR16 FL(EYC)	3.0 lbs.

120 VOLT MODELS WITH INTEGRATED ELECTRONIC 75 WATT TRANSFORMER AVAILABLE. ADD **-T** TO PART NUMBER  
NOTE: LED LIGHT BULBS ARE NOT COMPATIBLE WITH **-T** MODELS



**DL-20-MR16-BRS**  
mounted on  
FA-24-BRS



## MOUNTING ACCESSORIES

FA-01/BRS, FA-03-RX/-BRS, FA-03/BRS, FA-03-LG, FA-24-MD-CST-PC/-BRS, FA-24-MD-CST/-BRS, FA-22-CST / -BRS, FA-22 / -BRS, FA-24/BRS, FA-30-4, FA-30-8, FA-24MD-CST-TREE (10"-41"), FA-111, FA-24-TREE, FA-24-LG-SPUN-BRS, FA-24-LG-CST-BRS, FA-111-TREE (10"-41"), FA-22-TREE (10"-41"), FA-24-TREE, FA-30, FA-31, FA-32, FA-33, FA-34 -BRS = Brass Models (Arrow: couplers)

## BEAM/GLARE CONTROL ACCESSORIES

FA-08-06	Round 1/4" Hex Cell Louver
FA-10-20-BLUE	Blue Tempered Glass Lens
FA-10-20-GREEN	Green Tempered Glass Lens
FA-94	6" Extra-Long Extension Shield (aluminum only)
FA-98-20	Linear Spread Tempered Glass Lens
FA-104-20	Wide Spread Tempered Glass Lens Softener

## JOB INFORMATION

Type: \_\_\_\_\_ Date: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. No.: \_\_\_\_\_

Lamp(s): \_\_\_\_\_

Specifier: \_\_\_\_\_

Contractor: \_\_\_\_\_

Notes: \_\_\_\_\_

FOCUS INDUSTRIES INC. 25301 COMMERCE DRIVE LAKE FOREST, CA 92630  
www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390

Powder Coat Finishes	Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta
Ordering Code	-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC

**LIGHT DISTRIBUTIONS AND PHOTOMETRICS**
