



DIRECTIONAL LIGHTS DL-30-NL HID SERIES

TYPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum or cast brass Bullet; matching heavy duty cast aluminum or brass adjustable swivel

LENS: High impact clear tempered convex glass

LAMP SUPPLIED: None (100w max); Use only outdoor rated PAR30 lamps

SOCKET: Medium base high temperature ceramic 600v, 660w 4 K.V. pulse rated. Brass nickel-plate screw shell with 150°C lead wires


WIRING: Standard 120v Black, White and Ground 9" lead wires

MOUNTING: None supplied. See Mounting Accessories below for options

FINISH: Aluminum-Black texture polyester powder coat. Optional finishes available Brass-Unfinished brass. Optional finishes available

DOWN LIGHTS: Add -D suffix to catalog number for down light without weep holes.


NOTE: Remote ballast required to correspond with PAR30 HID lamp to be used. Consult factory for Above Grade and Direct Burial ballast options.



DL-30-NL-EC-HID



**DOWN LIGHT
APPLICATION
AVAILABLE**



DL-30-NL-AC-HID



DL-30-NL-HID-BRS

IP54



ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-30-NL-ECHID-BLT	Cast Aluminum HID PAR30 Bullet, extension collar	None	3.0 lbs.
DL-30-NL-ECHID-BRS	Cast Brass HID PAR30 Bullet, extension collar	None	5.0 lbs.
DL-30-NL-ACHID-BLT	Cast Aluminum HID PAR30 Bullet, angle collar	None	4.0 lbs.
DL-30-NL-ACHID-BRS	Cast Brass HID PAR30 Bullet, angle collar	None	6.0 lbs.

MOUNTING ACCESSORIES

C/FA-25-/26/BRS

C/FA-26-GFIC/BRS

C/FA-39/BRS

FA-111

FA-22-CST-/BRS
FA-22-/BRS

FA-24-LG-CST / -BRS
FA-24-LG-SPUN / -BRS

FA-24-MD-CST-PC-/BRS

FA-24-MD-CST-/BRS

FA-22-TREE
(10"-41")

FA-111-TREE
(10"-41")

FA-30 FA-31 FA-32 FA-33 FA-34
-BRS = Brass Models (Arrow: couplers)
STEM EXTENSIONS

BEAM/GLARE CONTROL ACCESSORIES

FA-08-30	Round 1/4" Hex Cell Louver
FA-10-30-BLUE	Blue Tempered Glass Lens
FA-10-30-GREEN	Green Tempered Glass Lens
FA-40	Aluminum Extension Cap, Tempered Convex Glass Lens
FA-40-AC	Aluminum Angle Cap, Tempered Convex Glass Lens
FA-95	6" Extra-Long Extension Shield (aluminum only)
FA-98-30	Linear Spread Tempered Glass Lens
FA-104-30	Wide Spread Tempered Glass Lens Softener

JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC.
25301 COMMERCENTRE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC	-BAR/CAR	-BAV/CAV	-BAT