


NOTE: To prevent electrical shock, disconnect transformer from electrical supply before installation or service.

1. Drill a 1/4" hole in wall or vertical surface to run 18/2 lead wire through and connect wire to 12V power supply.
2. Using #2 Phillips screw driver attach #6 X 1-1/4" Phillips wood screw provided to wall leaving screw head approximately 1/8" from surface. Use plastic wall anchors for brick, block, stone or concrete applications.
3. Slide fixture onto screw and pull down so screw sits in key hole.
4. Using the second provided #6 screw, secure fixture to wall through notch in bottom of fixture.
6. Install lamp (see instructions below.)
7. Connect 18/2 black fixture wire to main 12/2, 10/2 or 8/2 using approved gel filled direct burial wire nuts.
8. Turn on 12v power and check for light output.

CAUTION: If using OMNI LED, fixture must be connected to magnetic transformer only. OMNI LED not compatible with electronic transformers.



LIGHT BULB INSTALLATION/REPLACEMENT

Note: For easier access to lamp, remove bottom screw and rotate fixture so socket and lamp are visible.

1. Turn off power to fixture and let lamp cool down.
2. For S-8, T-3, & T-4 S.C. lamps press and rotate counter clockwise to release lamp. Reverse procedure to install new lamp. For Bi-Pin halogen, pull light bulb away from socket to release and insert new lamp with pins aligned with socket.
3. Reverse procedure to re-install new light bulb. Note: Replace lamp with correct type and wattage marked on fixture label.
4. Reinstall bottom screw if removed and tighten screws with Phillips #2 screwdriver.

CAUTION: Do not exceed maximum wattage marked on fixture label.



IMPORTANT SAFETY INSTRUCTIONS TO REDUCE THE RISK OF FIRE AND INJURY TO PERSONS:

1. Lamp gets hot quickly; turn off, unplug/disconnect and allow to cool down before replacing the light bulb.
2. **DO NOT** touch hot lens, use guard or enclosure.
3. **DO NOT** look into lamp when on.
4. Keep lamp away from materials that may burn.
5. Use only with wattage/lamp marked on fixture warning and instructions.
6. Use the correct light bulb base with the correct socket.
7. **DO NOT** touch lamp at anytime. Use a lint-free cloth when handling the Halogen light bulbs as oil from skin may damage lamp and shorten lamp life.