



DIRECTIONAL LIGHTS DL-15 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum, cast brass or composite flood; matching cast aluminum, brass or composite adjustable swivel

REFLECTOR: Diamond embossed specular aluminum

LENS: High impact clear acrylic

LAMP SUPPLIED DL-15-H: 35 watt Halogen D.C. - 10,000 hours average rating (75w max.)

LAMP SUPPLIED DL-15-SC: 18 watt S8 #1141 S.C. - 1200 hours average rating (25w max.)

LAMP OPTIONS DL-15-SC: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or 3w 50,000 hours average rating OMNI-3 LED (-LED3)

SOCKET: Double contact bayonet base (Ba15d) or Single contact bayonet base (Ba15s).

Both with brass nickel plated lamp socket screw shell and 200°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only) 12v only

MOUNTING: FA-03 black 9" ABS stake threaded 1/2" NPS


FINISH: Aluminum-Black texture polyester powder coat. Optional finishes available. Brass-Unfinished brass. Optional finishes available.




DL-15-SC-BRT
mounted on
FA-25-BRT

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	EST. SHIP WEIGHT
DL-15-H-BLT	Aluminum floodlight	35w T4 D.C. Halogen	2.0 lbs.
DL-15-H-BRS	Brass floodlight	35w T4 D.C. Halogen	3.0 lbs.
CDL-15-H-BLT	Composite floodlight	35w T4 D.C. Halogen	2.0 lbs.
DL-15-SC-BLT	Aluminum floodlight	18w S8 #1141	2.0 lbs.
DL-15-SC-BRS	Brass floodlight	18w S8 #1141	3.0 lbs.
CDL-15-SC-BLT	Composite floodlight	18w S8 #1141	2.0 lbs.



MOUNTING ACCESSORIES



BEAM/GLARE CONTROL

FA-07-15	Square 1/4" Hex Cell Louver
FA-10-15BLUE	Blue Tempered Glass Lens
FA-10-15GREEN	Green Tempered Glass Lens

JOB INFORMATION

Type:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	

FOCUS INDUSTRIES INC.
25301 COMMERCE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT






DIRECTIONAL LIGHTS DL-15 SERIES



TYPE

PHOTOMETRICS



Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT