



# DIRECTIONAL LIGHTS DL-17-RB-SS

TYPE

## SPECIFICATIONS

**CONSTRUCTION:** Cast 316 Stainless Steel Bullet; 316 Stainless Steel adjustable swivel with 360° rotation.

**LENS:** High impact clear tempered convex glass

**O-RING:** High temperature red silicone

**LAMP SUPPLIED:** 20w MR11 FL(FTD) 2000 hours average rating (35w max)

**LAMP OPTIONS:** We recommend 2w MR11 ARROW LED 50,000 hours average rating  
20w MR11 ULTRA 10,000 hours average rating

**SOCKET:** High temperature ceramic bi-pin GU5.3 with 250°C silicone lead wires


**WIRING:** Black 3 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

**CONNECTION:** FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

**MOUNTING:** FA-03 black 9" ABS stake threaded 1/2" NPS

**FINISH:** Machined stainless steel



## ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	EST. SHIP WEIGHT
DL-17-RB-SS	316 Stainless Steel Bullet	20w MR11 FL(FTD)	2.0 lbs.




## MOUNTING ACCESSORIES

## BEAM/GLARE CONTROL ACCESSORIES

- FA-08-17 Round 1/8" Hex Cell Louver
- FA-10-17-BLUE Blue Tempered Glass Lens
- FA-10-17-GREEN Green Tempered Glass Lens
- FA-98-17 Linear Spread Tempered Glass Lens
- FA-99-17 Convex Tempered Glass Lens
- FA-104-17 Wide Spread Tempered Glass Lens Softener

## LIGHT DISTRIBUTIONS AND PHOTOMETRICS



## JOB INFORMATION

Type: \_\_\_\_\_ Date: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. No.: \_\_\_\_\_

Lamp(s): \_\_\_\_\_

Specifier: \_\_\_\_\_

Contractor: \_\_\_\_\_

Notes: \_\_\_\_\_

FOCUS INDUSTRIES INC.  
25301 COMMERCENTRE DRIVE  
LAKE FOREST, CA 92630

www.focusindustries.com  
sales@focusindustries.com  
(949) 830-1350 • FAX (949) 830-3390