



landscape • entertainment • architectural • hospitality • illumination

DL-42/43/45/46 SERIES DIRECTIONAL LIGHT





DIRECTIONAL LIGHTS

DL-43-LEDM11



TYPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum or cast brass integrated heat sink base; matching cast adjustable swivel with 240° rotation; extruded aluminum, brass or copper housing (copper housing has brass base)

LENS: High impact clear tempered convex glass

O-RING: 2x high temperature red silicone

LIGHT SOURCE: 50,000 hour Integrated 2700K 600 lumen 11w LED module (equivalent to 50w halogen) with 6 high power Cree XPE LEDs

OPTICS: Interchangeable 15° spot, 40° flood, 60° wide flood and 160° widest flood (no optics)

12v DRIVER: Integrated on-board, no external driver required. 12v AC/DC input

120v DRIVER: HW-12-60LED* 120v AC input, 12v AC output LED driver

120v/277v DRIVER: HW-12-20MVLED* 90v-277v AC Input, 12v DC output LED driver

*Must use FA-26 mounting post or junction box

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

MOUNTING: Aluminum model: FA-03 black 9" ABS stake, tapped 1/2" NPS
Brass & Copper models: FA-03-LG large black 9" ABS stake, tapped 1/2" NPS

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available.
Brass & Copper - Unfinished. Optional finishes available.

NOTE: All LED modules are field exchangeable after production date September 1st, 2017.


GO GREEN



DL-43-LEDM1140-BLT

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-43-LEDM1115-BLT	Aluminum Bullet, 15° Optics	11w LED Module	3.0 lbs.
DL-43-LEDM1140-BLT	Aluminum Bullet, 40° Optics	11w LED Module	3.0 lbs.
DL-43-LEDM1160-BLT	Aluminum Bullet, 60° Optics	11w LED Module	3.0 lbs.
DL-43-LEDM11WF-BLT	Aluminum Bullet, No Optics	11w LED Module	3.0 lbs.
DL-43-LEDM1115-BRS	Brass Bullet, 15° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1140-BRS	Brass Bullet, 40° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1160-BRS	Brass Bullet, 60° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM11WF-BRS	Brass Bullet, No Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1115-COP	Copper Bullet, 15° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1140-COP	Copper Bullet, 40° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1160-COP	Copper Bullet, 60° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM11WF-COP	Copper Bullet, No Optics	11w LED Module	5.0 lbs.



DL-42 | DL-43 | DL-45

Beam Type	Angle	Visual Indicator
Spot	15°	Red Dot
Flood	40°	Green Dot
Wide Flood	60°	Blue Dot

IP65



BEAM/GLARE CONTROL ACCESSORIES

FA-08-DL-42-21	Round 1/4" Hex Cell Louver
FA-35-DL-42-GREEN	Green Acrylic Insert Lens
FA-11-DL-42-BLUE	Blue Tempered Glass Insert Lens
FA-11-DL-42-GREEN	Light Green Tempered Glass Insert Lens
FA-11-DL-42-AMBER	Amber Tempered Glass Insert Lens
FA-11-DL-42-RED	Red Tempered Glass Insert Lens
FA-104-DL-42-SB	Wide Spread Sandblasted Glass Insert Lens Softener



JOB INFORMATION	
Type:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	
FOCUS INDUSTRIES INC.* 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630 www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390	

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT



DIRECTIONAL LIGHTS

DL-43-LEDM11

TYPE

ORDERING INFORMATION - EXTERNAL DRIVERS

CATALOG NO.	DESCRIPTION
HW-12-60LED*	120v Input, 12v AC output LED Driver
HW-12-20MVLED*	90v-277v Input, 12v DC output LED Driver

*Must use FA-26 mounting post or junction box

HW-12-60LED | 2.25" (w) x 1.25" (h) x .75" (d)

HW-12-20MVLED | 6" (w) x 1.5" (h) x .11" (d)



MOUNTING ACCESSORIES

FA-03-BRS: 2" 51mm, 9.00" 229mm

FA-03-RX-BRS: 2" 51mm, 7.00" 178mm

FA-03-LG: 3" 76mm, 9.00" 229mm

FA-24-BRS: 3" 76mm, 0.9" 23mm

FA-22-CST-BRS: 3.50" 89mm, 1.125" 29mm

FA-24MD-CST-TREE /-BRS (10"-41")

FA-24-MD-CST-BRS: 2.65" 67mm, 1.4" 36mm

FA-24-MD-CST-PC/-BRS: 2.65" 67mm, 1.4" 36mm

FA-22-TREE /-BRS (10"-41")

FA-151-TREE /-BRS (10"-41")

FA-24-LG-CST/-BRS: 4.75" 121mm, 0.875" 22mm

FA-24-LG-SPUN-COP

FA-24-MD-CST-POST/-BRS: 1.63" 41mm, 15" 381mm

FA-24-MD-CST-POST2/-BRS (telescopic): 13" 330mm, 2.65" 67mm

C/FA-25/-26/-BRS: 20" 508mm, 3" 76mm

FA-30-4-PVC/-BRS: 4" 102mm

FA-30-8-PVC/-BRS: 8" 203mm

STEM EXTENSIONS: 10" 254mm, 13" 330mm, 16" 406mm, 21" 533mm, 26" 660mm

FA-30 FA-31 FA-32 FA-33 FA-34
-BRS = Brass Models (Arrow: couplers)

LIGHT DISTRIBUTIONS AND PHOTOMETRICS

