



PUTTING GREEN LIGHTS PGL-02 SERIES

TYPE

SPECIFICATIONS

CONSTRUCTION: Extruded aluminum or stamped brass body with cast aluminum or brass adjustable swivel; matching extruded aluminum or brass stanchion

REFLECTOR: Diamond embossed specular aluminum

LENS: High impact clear tempered flat glass

GASKET: None

LAMP SUPPLIED: 35w T-4 DC halogen; 10,000 hours rating (50w max.)

LAMP OPTIONS: 50w T-4 DC halogen; 2,000 hours rating

SOCKET: Double contact bayonet, brass nickel plated lamp socket screw shell (Ba15s) with 200°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)


FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available
Brass - Unfinished. Optional finishes available




ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
PGL-02-BLT	Aluminum Putting Green Light	35w T4 Halogen	3.0 lbs.
PGL-02-BRS	Brass Putting Green Light	35w T4 Halogen	5.0 lbs.

LIGHT DISTRIBUTIONS AND PHOTOMETRICS



35w T-4 DC Halogen



PGL-02 Light Distribution

JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630
www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC	-BAR/CAR	-BAV/CAV	-BAT