



# CUSTOM MARKER LIGHT SL-20-SMM1/2/3 SERIES



TYPE

## SPECIFICATIONS

### CONSTRUCTION:

**BODY:** Fiberglass reinforced bronze composite with molded brass inserts for screws

**MARKER DOME:** Cast aluminum only. Not available in brass option. Overall cover

height is 1.25", it is .875" from top of screw ledge

**LENS:** High impact clear tempered convex glass

**O-RING:** High temperature red silicone

**REFLECTOR:** Highly polished specular aluminum

**12v LAMP SUPPLIED:** 40,000 hour 3w ARROW Super Saver MR16 LED (-LED3)

**12v LAMP OPTIONS:** We recommend 40,000 hour 5w (-LED5) or 7w (-LED7) ARROW Super Saver MR16 LED or 5,000 hour 20w MR16 FL(BAB) Halogen

**12v SOCKET:** High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

**12v WIRING:** Black 4 foot 18/2 zip cord from base of fixture

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

**120v LAMP SUPPLIED:** None, use only outdoor rated PAR20 lamps

**120v LAMP OPTIONS:** We recommend 50,000 hour 9w ARROW PAR20 LED

**120v SOCKET:** High temperature ceramic medium base with 250°C silicone lead wires


**120v WIRING:** Standard 120v Black, White and Ground 9" lead wires

**CONNECTION:** FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only) 12v only

**FINISH:** Aluminum - Black texture polyester powder coat. Optional finishes available

Brass - Unfinished brass. Optional finishes available




TOP VIEW

SL-20-SMM-MR16-CPR

## ORDERING INFORMATION


CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
SL-20-SMM1-MR16LED3-BLT	Well Light, Aluminum Marker 1 Window (72°)	3w MR16 LED 36° FL	2.0 lbs.
SL-20-SMM2-MR16LED3-BLT	Well Light, Aluminum Marker 2 Window (144°)	3w MR16 LED 36° FL	2.0 lbs.
SL-20-SMM3-MR16LED3-BLT	Well Light, Aluminum Marker 3 Window (216°)	3w MR16 LED 36° FL	2.0 lbs.




BOTTOM  
2 Female 1/2" NPS threaded  
ports available upon request

For 120v No Lamp Par 20 models replace "MR16" in part number with "NL120V"


For standard 360° marker light remove the number 1, 2 or 3 after "SMM" from part number




SL-20-SMM  
Light Distribution



SL-20-SMM1  
Light Distribution



SL-20-SMM2  
Light Distribution



SL-20-SMM3  
Light Distribution

IP65

CE



### JOB INFORMATION

Type:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	

FOCUS INDUSTRIES INC.  
25301 COMMERCE DRIVE  
LAKE FOREST, CA 92630

www.focusindustries.com  
sales@focusindustries.com  
(949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT

SL-20-SMM1/2/3 Cut Sheet 081518

BRASS & COPPER ONLY