



CUSTOM MARKER LIGHT SL-20-SMM -1/-2/-3



TYPE

SPECIFICATIONS

CONSTRUCTION:

BODY: Fiberglass reinforced bronze composite with molded brass inserts for screws

MARKER DOME: Cast aluminum only. Not available in brass option

LENS: High impact clear tempered convex glass

O-RING: High temperature red silicone

REFLECTOR: Highly polished specular aluminum

12v LAMP SUPPLIED: 20w MR16 FL(BAB) 5000 hours average rating (50w max)

12v LAMP OPTIONS: We recommend 20 watt MR16 ULTRA10,000 hours average rating;
20w MR16 TITAN 18,000 hours average rating; 4w ARROW LED 50,000 hours average rating

12v SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

12v WIRING: Black 4 foot 18/2 zip cord from base of fixture

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

120v LAMP SUPPLIED: None, use only outdoor rated PAR20 lamps

120v LAMP OPTIONS: We recommend 9w ARROW LED PAR20 50,000 hours average rating


120v SOCKET: High temperature ceramic medium base with 250°C silicone lead wires

120v WIRING: Standard 120v Black, White and Ground 9" lead wires

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only) 12v only

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available



TOP VIEW


SL-20-SMMMR16-CPR

ORDERING INFORMATION


CATALOG NO.	DESCRIPTION	LAMP SUPPLIED	SHIP WEIGHT
SL-20-SMM1MR16-BLT	Well Light, Aluminum Marker 1 window (72°)	20w MR16 FL(BAB)	2.0 lbs.
SL-20-SMM2MR16-BLT	Well Light, Aluminum Marker 2 window (144°)	20w MR16 FL(BAB)	2.0 lbs.
SL-20-SMM3MR16-BLT	Well Light, Aluminum Marker 3 window (216°)	20w MR16 FL(BAB)	2.0 lbs.

For 120v No Lamp Par 20 models replace "MR16" in part number with "NL120V"


For standard 360° marker light remove the number 1, 2 or 3 after "SMM" from part number




BOTTOM
2 Female 1/2" NPS threaded
ports available upon request




SL-20-SMM
Light Distribution



SL-20-SMM1
Light Distribution



SL-20-SMM2
Light Distribution



SL-20-SMM3
Light Distribution

IP65

CE

ETL LISTED US

JOB INFORMATION

Type:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	

FOCUS INDUSTRIES INC.
25301 COMMERCE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT