

COMMERCIAL BRICK LIGHT SL-31 12 VOLT SERIES



SPECIFICATIONS

CONSTRUCTION:

FACE PLATE: Cast aluminum or brass

BACK BOX: Aluminum models- Cast aluminum powder coated high reflective white

Brass models- Unfinished cast brass LENS: High impact white acrylic

LENS MR16 MODELS: Linear spread glass

GASKET: Black neosponge closed cell; .190" thickness

LAMP SUPPLIED: 2 x 18w S8 #1141; 1200 hours average rating (25w max.)

LAMP SUPPLIED MR16 MODELS: 20w MR16 FL(BAB); 5000 hours rating (20w max.)

LAMP OPTIONS: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or

3w 50,000 hours average rating OMNI-3 LED (-LED3)

LAMP OPTIONS MR16 MODELS: We recommend ARROW 4w LED (-LED) or 6w LED

(-LED6W); 50,000 hour or ARROW SAVER 4w LED (-LAS); 40,000 hour

SOCKET: Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s) with

200°C silicone lead wires

SOCKET MR16 MODELS: High temp ceramic GU5.3 bi-pin with 250°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only)

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available

Brass - Unfinished. Optional finishes available

NOTE: 1/2" to 3/4" conduit fitting back holes and end holes available for feed through.

Specify requirements at time of order.









ORDERING INFORMATION									
CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT						
SL-31-BLT	Cast Aluminum 1 Louver Brick Light	18w S8 #1141	3.0 lbs.						
SL-31-BRS	Cast Brass 1 Louver Brick Light	18w S8 #1141	7.0 lbs.						
SL-31-MR16-BLT	Cast Alum 1 Louver Brick Light	20w MR16 FL(BAB)	3.0 lbs.						
SL-31-MR16-BRS	Cast Brass 1 Louver Brick Light	20w MR16 FL(BAB)	7.0 lbs.						

3.5"	7.25"	2.5"
89mm	184mm	64mm
<u> </u>	-	+
		<u> </u>
		ــــــــــــــــــــــــــــــــــــــ
†		†
	SL-08 Back	Вох

1/2" to 3/4" conduit fitting back holes and end holes available for feed through





SL-31: Mounting Holes on all models 7-1/2" on center



BACK BOX/SO	BACK BOX/SOCKET/LAMP ONLY											
CATALOG NO.	DESCRIPTION	LAMP										
FA-60	Cast Aluminum back box with lamp and socket	2x 18w S8 #1141										
FA-60-H	Cast Aluminum back box with lamp and socket	2x 20w halogen SC										
FA-60-X	Cast Aluminum back box with lamp and socket	2x 20w xenon SC										
FA-60-MR16	Cast Aluminum back box with lamp and socket	20w MR16 FL(BAB)										
FA-60-NL	Cast Aluminum back box with socket	None, 2 x Ba15s sockets										
FA-60-BRS	Cast Brass back box with lamp and socket	2x 18w S8 #1141										
FA-60-H-BRS	Cast Brass back box with lamp and socket	2x 20w halogen SC										
FA-60-X-BRS	Cast Brass back box with lamp and socket	2x 20w xenon SC										
FA-60-MR16-BRS	Cast Brass back box with lamp and socket	20w MR16 FL(BAB)										
FA-60-NL-BRS	Cast Brass back box with socket	None, 2 x Ba15s sockets										

	Intertex
JOB INFORMATION	
Туре:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	
FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630	www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390


Black Texture Antique (Standard) Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT -ATV	-BRT	-CAM	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT

SL-31 12V Cut Sheet 100915


BRASS & COPPER ONLY

COMMERCIAL BRICK LIGHT SL-31 12 VOLT SERIES

LIGHTING DISTRIBUTIONS AND PHOTOMETRICS



SL-31 Half Spread Photometrics



SL-31 Half Spread Photometrics

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-САМ	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT
SL-31 12V Cut	Sheet 10091	5										BRAS	S & COPPER ONI	Υ