



# DIRECTIONAL LIGHTS

## DL-50-LEDM17



TYPE

### SPECIFICATIONS

**CONSTRUCTION:** Cast aluminum or cast brass integrated heat sink base; matching cast adjustable swivel with 240° rotation; extruded aluminum or brass housing

**LENS:** High impact clear tempered convex glass

**O-RING:** 2x High temperature red silicone

**LIGHT SOURCE:** Integrated 1800 lumen 17w LED module (equivalent to 100w halogen) with 6 high power LEDs; 50,000 hours average rating. 3000k color temperature. 5 year warranty

**OPTICS:** Interchangeable spot (15°), flood (40°), wide flood (60°) and 160° very wide flood (no optics)

**120v-277v DRIVER:** Integrated on-board, no external driver required. 120v 277vAC input

**WIRING:** Standard 120 volt Black, White and Ground 9" lead wires

**MOUNTING:** None supplied. We recommend FA-26 mounting pedestal


**FINISH:** Aluminum - Black texture polyester powder coat. Optional finishes available.

Brass - Unfinished. Optional finishes available.



### ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-50-LEDM1715-BLT	Aluminum Bullet, 15° Optics	17w LED Module	3.0 lbs.
DL-50-LEDM1740-BLT	Aluminum Bullet, 40° Optics	17w LED Module	3.0 lbs.
DL-50-LEDM1760-BLT	Aluminum Bullet, 60° Optics	17w LED Module	3.0 lbs.
DL-50-LEDM17WF-BLT	Aluminum Bullet, No Optics	17w LED Module	3.0 lbs.
DL-50-LEDM1715-BRS	Brass Bullet, 15° Optics	17w LED Module	5.0 lbs.
DL-50-LEDM1740-BRS	Brass Bullet, 40° Optics	17w LED Module	5.0 lbs.
DL-50-LEDM1760-BRS	Brass Bullet, 60° Optics	17w LED Module	5.0 lbs.
DL-50-LEDM17WF-BRS	Brass Bullet, No Optics	17w LED Module	5.0 lbs.



DL-50-LEDM

Beam Type	Angle	Visual Indicator
Spot	15°	Red Dot
Flood	40°	Green Dot
Wide Flood	60°	Blue Dot



### BEAM/GLARE CONTROL ACCESSORIES

FA-08-DL-42-21	Round 1/4" Hex Cell Louver
FA-35-DL-42-GREEN	Green Acrylic Insert Lens
FA-11-DL-42-BLUE	Blue Tempered Glass Insert Lens
FA-11-DL-42-GREEN	Light Green Tempered Glass Insert Lens
FA-11-DL-42-AMBER	Amber Tempered Glass Insert Lens
FA-11-DL-42-RED	Red Tempered Glass Insert Lens
FA-104-DL-42-SB	Wide Spread Sandblasted Glass Insert Lens Softener



### JOB INFORMATION

Type: \_\_\_\_\_ Date: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. No.: \_\_\_\_\_

Lamp(s): \_\_\_\_\_

Specifier: \_\_\_\_\_

Contractor: \_\_\_\_\_

Notes: \_\_\_\_\_

FOCUS INDUSTRIES INC.®  
 25301 COMMERCENTRE DRIVE  
 LAKE FOREST, CA 92630

www.focusindustries.com  
 sales@focusindustries.com  
 (949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT