



PENDANT LIGHTS RXS-18P SERIES

TYPE



SPECIFICATIONS

CONSTRUCTION:

ALUMINUM: Aluminum Canister with matching extruded aluminum stem; includes cast FA-24-MDCST aluminum canopy for 12v and cast FA-24-LGCST aluminum canopy for 120v

BRASS: Brass Canister with matching extruded brass stem; includes cast FA-24-MDCST brass canopy for 12v and cast FA-24-LGCST brass canopy for 120v

COPPER: Copper Canister with matching extruded copper stem; includes FA-24-MDSPUNCOP copper canopy for 12v and FA-24-LGSPUNCOP copper canopy for 120v

LENS: High impact clear tempered flat glass

O-RING: High temperature red silicone

LIGHT SOURCE: 50,000 hour integrated LED module:

7w - 450 lumen, 3000K warm white (equivalent to 35w Halogen)

11w - 600 lumen, 3000K warm white (equivalent to 50w Halogen)

15w - 900 lumen, 3000K warm white (equivalent to 75w Halogen)

OPTICS: 15° spot, 40° flood, 60° wide flood or 160° widest flood (no optics)

12v DRIVER: Integrated on-board, no external driver required. 12vAC/DC input

120v DRIVER: Internal 120vAC input, 12vAC output LED driver

120v/277v DRIVER: External 90-277vAC Input, 12vDC output LED driver

SOCKET: LED module - integrated hard wire, no socket

WIRING 12v: Black 4 foot 18/2 zip cord from base of fixture

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

WIRING 120v: Standard 120v Black/White/Green wiring inside fixture housing.

MOUNTING: FA-24-MDCST or FA-24-LGCST canopy with mounting hardware supplied

FINISH: Aluminum - Black texture polyester powder coat, optional finishes available


Brass and Copper - Unfinished, optional finishes available



RXS-18P with
FA-RXS3LENSB

OPTICS DETAILS:

Beam Type	Angle	Visual Indicator
Spot	15°	Red Dot
Flood	40°	Green Dot
Wide Flood	60°	Blue Dot



RXS-18P
(12v)

RXS-18P
(120v)

BEAM/GLARE CONTROL ACCESSORIES

FA-08-06	Round 1/4" Hex Cell Louver
FA-10-20-BLUE	Blue Tempered Glass Lens
FA-10-20-GREEN	Green Tempered Glass Lens
FA-98-20	Linear Spread Tempered Glass Lens
FA-104-20	Wide Spread Tempered Glass Lens Softener
FA-RXS3LENS	3"Ø x 3.5" Clear Acrylic Lens
FA-RXS3LENSB	3"Ø x 3.5" Sand Blast Acrylic Lens



JOB INFORMATION

Type:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	

FOCUS INDUSTRIES INC.
25301 COMMERCENTRE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT



PENDANT LIGHTS RXS-18P SERIES

TYPE

ORDERING INFORMATION				
CATALOG NUMBER	DESCRIPTION	OPTICS PACKAGE	LIGHT SOURCE	SHIP WEIGHT
RXS-18P-LEDM7WF-BLT	Aluminum Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	7w LED Module	4.0 lbs.
RXS-18P-LEDM715-BLT	Aluminum Pendant Fixture	15° SPOT OPTICS	7w LED Module	4.0 lbs.
RXS-18P-LEDM740-BLT	Aluminum Pendant Fixture	40° FLOOD OPTICS	7w LED Module	4.0 lbs.
RXS-18P-LEDM760-BLT	Aluminum Pendant Fixture	60° WIDE FLOOD OPTICS	7w LED Module	4.0 lbs.
RXS-18P-LEDM7WF-BRS	Brass Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	7w LED Module	6.0 lbs.
RXS-18P-LEDM715-BRS	Brass Pendant Fixture	15° SPOT OPTICS	7w LED Module	6.0 lbs.
RXS-18P-LEDM740-BRS	Brass Pendant Fixture	40° FLOOD OPTICS	7w LED Module	6.0 lbs.
RXS-18P-LEDM760-BRS	Brass Pendant Fixture	60° WIDE FLOOD OPTICS	7w LED Module	6.0 lbs.
RXS-18P-LEDM7WF-COP	Copper Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	7w LED Module	5.0 lbs.
RXS-18P-LEDM715-COP	Copper Pendant Fixture	15° SPOT OPTICS	7w LED Module	5.0 lbs.
RXS-18P-LEDM740-COP	Copper Pendant Fixture	40° FLOOD OPTICS	7w LED Module	5.0 lbs.
RXS-18P-LEDM760-COP	Copper Pendant Fixture	60° WIDE FLOOD OPTICS	7w LED Module	5.0 lbs.
RXS-18P-LEDM11WF-BLT	Aluminum Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	11w LED Module	4.0 lbs.
RXS-18P-LEDM1115-BLT	Aluminum Pendant Fixture	15° SPOT OPTICS	11w LED Module	4.0 lbs.
RXS-18P-LEDM1140-BLT	Aluminum Pendant Fixture	40° FLOOD OPTICS	11w LED Module	4.0 lbs.
RXS-18P-LEDM1160-BLT	Aluminum Pendant Fixture	60° WIDE FLOOD OPTICS	11w LED Module	4.0 lbs.
RXS-18P-LEDM11WF-BRS	Brass Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	11w LED Module	6.0 lbs.
RXS-18P-LEDM1115-BRS	Brass Pendant Fixture	15° SPOT OPTICS	11w LED Module	6.0 lbs.
RXS-18P-LEDM1140-BRS	Brass Pendant Fixture	40° FLOOD OPTICS	11w LED Module	6.0 lbs.
RXS-18P-LEDM1160-BRS	Brass Pendant Fixture	60° WIDE FLOOD OPTICS	11w LED Module	6.0 lbs.
RXS-18P-LEDM11WF-COP	Copper Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	11w LED Module	5.0 lbs.
RXS-18P-LEDM1115-COP	Copper Pendant Fixture	15° SPOT OPTICS	11w LED Module	5.0 lbs.
RXS-18P-LEDM1140-COP	Copper Pendant Fixture	40° FLOOD OPTICS	11w LED Module	5.0 lbs.
RXS-18P-LEDM1160-COP	Copper Pendant Fixture	60° WIDE FLOOD OPTICS	11w LED Module	5.0 lbs.
RXS-18P-LEDM15WF-BLT	Aluminum Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	15w LED Module	4.0 lbs.
RXS-18P-LEDM1515-BLT	Aluminum Pendant Fixture	15° SPOT OPTICS	15w LED Module	4.0 lbs.
RXS-18P-LEDM1540-BLT	Aluminum Pendant Fixture	40° FLOOD OPTICS	15w LED Module	4.0 lbs.
RXS-18P-LEDM1560-BLT	Aluminum Pendant Fixture	60° WIDE FLOOD OPTICS	15w LED Module	4.0 lbs.
RXS-18P-LEDM15WF-BRS	Brass Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	15w LED Module	6.0 lbs.
RXS-18P-LEDM1515-BRS	Brass Pendant Fixture	15° SPOT OPTICS	15w LED Module	6.0 lbs.
RXS-18P-LEDM1540-BRS	Brass Pendant Fixture	40° FLOOD OPTICS	15w LED Module	6.0 lbs.
RXS-18P-LEDM1560-BRS	Brass Pendant Fixture	60° WIDE FLOOD OPTICS	15w LED Module	6.0 lbs.
RXS-18P-LEDM15WF-COP	Copper Pendant Fixture	160° WIDEST FLOOD (NO OPTICS)	15w LED Module	5.0 lbs.
RXS-18P-LEDM1515-COP	Copper Pendant Fixture	15° SPOT OPTICS	15w LED Module	5.0 lbs.
RXS-18P-LEDM1540-COP	Copper Pendant Fixture	40° FLOOD OPTICS	15w LED Module	5.0 lbs.
RXS-18P-LEDM1560-COP	Copper Pendant Fixture	60° WIDE FLOOD OPTICS	15w LED Module	5.0 lbs.

120v Input: add "120" to end of part number, prior to color code. For example, RXS-18P-LEDM715-120-BLT