

CIRCULAR PAVER LIGHTS SL-37-P-MR16 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Machined brass cylinder with threaded cap

LENS: High impact clear tempered step glass **O-RING**: High temperature red silicone

LAMP SUPPLIED: 40,000 hour 3w ARROW Super Saver MR16 LED (-LED3) **LAMP OPTIONS**: We recommend 40,000 hour 5w (-LED5) or 7w (-LED7) ARROW

Super Saver MR16 LED

SOCKET: High temperature ceramic bi-pin with 250°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only)


FINISH: Unfinished brass. Optional finishes available






ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
SL-37-P-MR16-LED3-BRS	Circular Brass Paver Light	3w MR16 LED 36° FL	2.0 lbs.







	Inte	rtek
JOB INFORMATION		
Type:	Date:	
Job Name:		
Cat. No.:		
Lamp(s):		
Specifier:		
Contractor:		
Notes:		
FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630	www.focusindustrie sales@focusindustrie (949) 830-1350 • FAX (949) 830	es.com

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/C	AR -BAV/CA	V -BAT