

CIRCULAR PAVER LIGHTS SL-37-P-MR16 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Machined brass cylinder with threaded cap

LENS: High impact clear tempered step glass **O-RING**: High temperature red silicone

LAMP SUPPLIED: 40,000 hour 3w ARROW Super Saver MR16 LED (-LED3) **LAMP OPTIONS**: We recommend 40,000 hour 5w (-LED5) or 7w (-LED7) ARROW

Super Saver MR16 LED

SOCKET: High temperature ceramic bi-pin with 250°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only)

FINISH: Unfinished brass. Optional finishes available


VEHICULAR PRESSURE RATING: 8800 lbs






ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT		
SL-37-P-MR16-LED3-BRS	Circular Brass Paver Light	3w MR16 LED 36° FL	2.0 lbs.		



SL-37-P-MR16





	Intertek
JOB INFORMATION	
Туре:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	
FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630	www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder		Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-1	BAR/CAR	-BAV/CAV	-BAT
CONTRACT A STATE OF THE STATE O										22466					

SL37PHVR16CuSheet 120718

BRASS & COPPER ONLY