



landscape • entertainment • architectural • hospitality • illumination

# PL-14 SERIES PATH LIGHT





# PATH LIGHTS PL-14 SERIES



TYPE

## SPECIFICATIONS

**CONSTRUCTION:** Heavy duty stamped brass 5.25" Pyramid hat; matching extruded square brass stanchion

**LAMP SUPPLIED:** 18w S8 #1141; 1200 hours average rating (25w max.)

**LAMP OPTIONS:** We recommend 3w 50,000 hours average rating OMNI-3 LED (-LED3) or OMNI-3 Super Saver (-LED3SS) 10,000 hours average rating 20w Xenon (-X) or 20w Halogen (-H)

**SOCKET:** Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s); double contact bayonet base (Ba15d) for 120v, both with 200°C silicone lead wires

**WIRING:** Black 3 foot 18/2 zip cord from base of fixture (12v only)  
For 25 foot 16/2 fixture lead wire add -25F to catalog number.  
120v standard wiring


**CONNECTION:** FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only) 12v only

**MOUNTING:** FA-03 black 9" ABS stake, tapped 1/2" NPS

**FINISH:** Unfinished brass. Optional finishes available



**PL-14-BRS**  
mounted on  
FA-24-BRS



## ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
PL-14-BRS	Stamped Brass 5.25" Pyramid Hat	18w S8 #1141	3.0 lbs.

### MOUNTING ACCESSORIES

**FA-03-RX/-BRS**  
7.00" 178mm

**FA-03/BRS**  
9.00" 229mm

**FA-03-LG**  
9.00" 229mm

**FA-24/BRS**  
0.9" 23mm

**FA-22-CST/-BRS**  
5.75" 146mm

**FA-22-BRS**  
1.125" 29mm

**FA-24-MD-CST/-BRS**  
2.65" 67mm

**FA-24-LG-CST / -BRS**  
4.75" 121mm

**FA-24-LG-SPUN / -BRS**  
0.875" 22mm

**FA-01/BRS**  
15" 381mm

**FA-24-MD-CST-POST2/-BRS**  
1.63" 41mm

**FA-24-MD-CST-POST2/-BRS (telescopic)**  
13" 330mm

**C/FA-25/-26/BRS**  
20" 508mm

**C/FA-26-75W/BRS**  
20" 508mm

**C/FA-26-GFIC/BRS**  
26" 660mm

**C/FA-39/BRS**  
20" 508mm

**FA-24-MD-CST-PC/-BRS**  
2.65" 67mm


**FA-30-4**  
4" 102mm

**FA-30-8**  
8" 203mm

**FA-30 FA-31 FA-32 FA-33 FA-34**  
10" 254mm, 13" 330mm, 16" 406mm, 21" 533mm, 26" 660mm  
-BRS = Brass Models (Arrow: couplers)

**STEM EXTENSIONS**

## LIGHT DISTRIBUTIONS AND PHOTOMETRICS



**PL-14**  
Half Spread Photometrics  
18 ft. (5.5m) diameter

## JOB INFORMATION

Type: \_\_\_\_\_ Date: \_\_\_\_\_

Job Name: \_\_\_\_\_

Cat. No.: \_\_\_\_\_

Lamp(s): \_\_\_\_\_

Specifier: \_\_\_\_\_

Contractor: \_\_\_\_\_

Notes: \_\_\_\_\_

**FOCUS INDUSTRIES INC.**  
25301 COMMERCENTRE DRIVE  
LAKE FOREST, CA 92630

[www.focusindustries.com](http://www.focusindustries.com)  
[sales@focusindustries.com](mailto:sales@focusindustries.com)  
(949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT