

SURFACE MOUNT RXS-03 SERIES

SPECIFICATIONS


CONSTRUCTION: Copper directional Bullet; matching stamped copper FA-111-SM J-box and adjustable aiming bracket LENS: High impact clear tempered convex glass O-RING: High temperature red silicone LAMP SUPPLIED: 20w MR8 (FL) 2000 hours average rating (20w max) LAMP OPTIONS: 20w MR8 (SP) 2000 hours average rating SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only) For 25 foot 16/2 fixture lead wire add -25F to catalog number. CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

MOUNTING: FA-111-SM surface mount J-box

FINISH: Unfinished Copper. Optional finishes available





ORDERING INFORMATION									
CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT						
RXS-03-COP	Copper Surface Mount Bullet with Aiming Bracket and J-Box	20w MR8 (FL)	2.0 lbs.						





LIGHT DISTRIBUTIONS AND PHOTOMETRICS







BEAM/GLARE CONTROL ACCESSORIES							JOB INFORMATION							
FA-08-23	Round 1/8	Round 1/8"Hex Cell Louver						Туре:			Date:			
FA-11-23-BLUE FA-11-23-GREEN									Job Name:					
FA-98-23 Linear Spread Tempered Glass Lens									Cat. No.:					
FA-104-23	Wide Spre	ad Tempere	ed Glass Lens	s Softener					Lamp(s):					
									Specifier:					
									Contractor:					
									Notes:					
								FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630			www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390			
Black Texture Antique (Standard) Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta	Acid Rust	Acid Verde	Black Acid Treatment
-BLT -ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC	-BAR/CAR	-BAV/CAV	
RXS-03-COP Cut Sheet	053112	1	1	1	1	1		1	1	1		BRAS	S & COPPER ON	ĹY