

LED STEP LIGHTS SL-02-LEDP SERIES

GOGREEN

SPECIFICATIONS

CONSTRUCTION: Stamped aluminum, brass, copper or stainless steel (-SS available only on SL-02 4 louver model) step/brick light with stamped stainless steel surface mounting bracket

3 LENS OPTIONS:

SL-02-LEDP: Standard white acrylic; creates warm 2700K incandescent like color SL-02-LEDP-SB: Sand Blast clear acrylic; creates soft 3000K halogen like color

SL-02-LEDP-CL: Clear acrylic; bright halogen 3000K color **GASKET:** Black neosponge closed cell; .190" thickness

LIGHT SOURCE: 12v, 4w integrated LED flat panel with external driver, warm white 3000K

350 lumens (3000K) / 380 lumens (5200K)

LIFETIME RATING: 50,000 hours

SOCKET: None

DRIVER: 4w output, 12v AC input. Maximum distance from fixture is 18 feet.

For use with magnetic transformers only

VOLTAGE RANGE: 9 to 18 volts. Optimum operating range of 10 to 15 volts for consistent

performance and brightness.

WIRING: Red(+) and Black(-) 18 gauge zip cord from LED panel. Connects to external driver

Red(+) and Black(-) 18 gauge zip cord.

Additional 6' 18/2 zip cord supplied for wiring external driver to main cable.

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from LED driver to main cable

(12/2, 10/2 or 8/2 only)

MOUNTING: Stainless Steel surface mount bracket; four screws and wall anchors provided;

Face plate attaches to bracket with two provided screws

FINISH: Aluminum - Black texture polyester powder coat; optional finishes available

Brass - Unfinished; optional finishes available Copper-Unfinished; optional finishes available

Stainless Steel-Brushed

CAUTION: MUST BE POWERED BY LOW VOLTAGE AC MAGNETIC TRANSFORMER ONLY

SL-02: Mounting Holes on all models 3-5/16" on center










SL-02-LEDPBRS



SL-02-1LLEDPBAR



		Intertek
JOB INFORMATION		
Type:	Date:	
Job Name:		
Cat. No.:		
Lamp(s):		
Specifier:		
Contractor:		
Notes:		
FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630	www.focusin sales@focusin (949) 830-1350 • FAX (9	dustries.com


Black Text (Standar	ure Antique d) Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT

ORDERING INFORMATION

ONDERING IN ORMATION											
CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT								
SL-02-LEDP-BLT	Aluminum 4 Louver Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-LEDP-BRS	Brass 4 Louver Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-LEDP-COP	Copper 4 Louver Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-LEDP-SS	Stainless Steel 4 Louver Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-AL-LEDP-BLT	Aluminum Lensed Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-AL-LEDP-BRS	Brass Lensed Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-AL-LEDP-COP	Copper Lensed Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-1L-LEDP-BLT	Aluminum 1 Louver Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-1L-LEDP-BRS	Brass 1 Louver Brick Light	4w Flat Panel LED	2.0 lbs.								
SL-02-1L-LEDP-COP	Copper 1 Louver Brick Light	4w Flat Panel LED	2.0 lbs.								

Lenses are all standard white acrylic; creates warm 2700K incandescent like color Add -SB To Part #: Sand Blast clear acrylic; creates soft 3000K halogen like color Add -CL To Part #: Clear acrylic; bright halogen 3000K color

Add -52 To Part #: 5200K Cool White Flat Panel LED







SL-02-AL-LEDP



STEP LIGHTS SL-02 SERIES

TYPE

LIGHT DISTRIBUTIONS AND PHOTOMETRICS

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-САМ	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT
SL-02-LEDPCutSheet 121015 BRASS & COPPER ONLY										Υ				