

SL-20-SM-M WELL LIGHTS

landscape • entertainment • architectural • hospitality • illumination







MARKER LIGHT SL-20-SMM SERIES



SPECIFICATIONS

CONSTRUCTION:

BODY: Fiberglass reinforced bronze composite with molded brass inserts for screws

MARKER DOME: Cast aluminum or cast brass:

Overall cover height is 1.25", it is .875" from top of screw ledge

LENS: High impact clear tempered convex glass

O-RING: High temperature red silicone

REFLECTOR: Highly polished specular aluminum

12v LAMP SUPPLIED: 20w MR16 FL(BAB) 5000 hours average rating (50w max)

12v LED OPTIONS: We recommend 3w, 5w or 7w Arrow Super Saver 12v MR16 LED, 40,000 hours

12v SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

12v WIRING: Black 4 foot 18/2 zip cord from base of fixture For 25 foot 16/2 fixture lead wire add -25F to catalog number.

120v LAMP SUPPLIED: None, use only outdoor rated PAR20 lamps

120v LED OPTIONS: We recommend 8w ARROW Super Saver LED PAR20 50,000 hours average

rating or 3w, 5w or 7w Arrow Super Saver 120v MR16 LED, 40,000 hours

120v SOCKET: High temperature ceramic medium base with 250°C silicone lead wires

120v WIRING: Standard 120v Black, White and Ground 9" lead wires

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only) 12v only

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available

Brass - Unfinished brass. Optional finishes available **VEHICULAR PRESSURE RATING: 8800 lbs**

LEDS by CREE€






SL-20-SMMMR16-CPR


IOD INFORMATION

ORDERING INFORMATION CATALOG NO. **DESCRIPTION** LAMP SUPPLIED SHIP WEIGHT SL-20-SMMMR16-BLT 20w MR16 FL(BAB) 2.0 lbs. Well Light, Aluminum Marker SL-20-SMMMR16-BRS Well Light, Brass Marker 20w MR16 FL(BAB) 3.0 lbs. SL-20-SMMNL120V-BLT Well Light, Aluminum Marker None 2.0 lbs. SL-20-SMMNL120V-BRS Well Light, Brass Marker 3.0 lbs. None





воттом 2 Female 1/2" NPS threaded ports available upon request



IP65	CE	C USTED US
1	-	Intertek

ACCESSORIES CATALOG NO. DESCRIPTION Round 1/4" Mini Hex Cell Louver FA-08-06 FA-10-SL20SMAMBER Flat Amber Tempered Glass Lens FA-10-SL20SMBLUE Flat Blue Tempered Glass Lens FA-10-SL20SMGREEN Flat Green Tempered Glass Lens FA-10-SL20SMRED Flat Red Tempered Glass Lens FA-FORM-SL20SM Concrete form for SL-20-SM Series

JOB INFORMATION				
Туре:	Date	2:		
Job Name:				
Cat. No.:				
Lamp(s):				
Specifier:				
Contractor:				
Notes:				
FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630	www.focusindustries.cor sales@focusindustries.cor (949) 830-1350 • FAX (949) 830-339			
Rubbed Chrome Verde Powder	Acid Rust	Acid Verde	Black Acid	

(Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder		Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-САМ	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR		-BAR/CAR	-BAV/CAV	-BAT
CL 20 SMM Cut Shoot									DDAC	C O CODDED ON	IV				

SL-20-SMM Cut Sheet 011/19 BRASS & COPPER ONLY