

CUSTOM MARKER LIGHT SL-20-SMM -1/-2/-3



SPECIFICATIONS

CONSTRUCTION:

BODY: Fiberglass reinforced bronze composite with molded brass inserts for screws

MARKER DOME: Cast aluminum only. Not available in brass option. Overall cover height is 1.25," it

is .875" from top of screw ledge

LENS: High impact clear tempered convex glass

O-RING: High temperature red silicone

REFLECTOR: Highly polished specular aluminum

12v LAMP SUPPLIED: 20w MR16 FL(BAB) 5000 hours average rating (50w max)

12v LED OPTIONS: We recommend 3w, 5w or 7w Arrow Super Saver 12v MR16 LED, 40,000 hours

12v SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

12v WIRING: Black 4 foot 18/2 zip cord from base of fixture For 25 foot 16/2 fixture lead wire add -25F to catalog number.

120v LAMP SUPPLIED: None, use only outdoor rated PAR20 lamps

120v LED OPTIONS: We recommend 8w ARROW Super Saver LED PAR20 50,000 hours average

rating or 3w, 5w or 7w Arrow Super Saver 120v MR16 LED, 40,000 hours

120v SOCKET: High temperature ceramic medium base with 250°C silicone lead wires

120v WIRING: Standard 120v Black, White and Ground 9" lead wires

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only) 12v only

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available

VEHICULAR PRESSURE RATING: 8800 lbs






TOP VIEW

SL-20-SMMMR16-CPR

ORDERING INFOR	RMATION				
CATALOG NO.	DESCRIPTION	LAMP SUPPLIED	SHIP WEIGHT		
SL-20-SMM1MR16-BLT	Well Light, Aluminum Marker 1 window (72°)	20w MR16 FL(BAB)	2.0 lbs.		
SL-20-SMM2MR16-BLT	Well Light, Aluminum Marker 2 window (144°)	20w MR16 FL(BAB)	2.0 lbs.		
SL-20-SMM3MR16-BLT	Well Light, Aluminum Marker 3 window (216°)	20w MR16 FL(BAB)	2.0 lbs.		


For 120v No Lamp Par 20 models replace "MR16" in part number with "NL120V"

For standard 360° marker light remove the number 1, 2 or 3 after "SMM" from part number





BOTTOM
2 Female 1/2" NPS threaded ports available upon request



SL-20-SMM Light Distribution



SL-20-SMM1 Light Distribution



SL-20-SMM2



SL-20-SMM3 Light Distribution

IP65	CE	
05		C US

	LISTED
JOB INFORMATION	
Туре:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	
FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630	www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390

										LAKE FORE	31, CA 9263C	1	(949) 830-13	50 • FAX (949)	830-3390
Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder		Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR		-BAR/CAR	-BAV/CAV	-BAT