

DIRECTIONAL SURFACE MOUNT SL-25 SERIES

ΤΥΡΕ

SPECIFICATIONS

CONSTRUCTION: Cast aluminum or brass directional bullet; matching stamped aluminum, or brass FA-111-SM J-box and adjustable aiming bracket

LENS: High impact clear tempered convex glass

O-RING: High temperature red silicone

LAMP SUPPLIED: 20w MR16 FL(BAB) 5000 hours average rating (50w max)

LAMP OPTIONS: We recommend ARROW 4w LED (-LED) or 6w LED (-LED6W); 50,000 hour or ARROW SAVER 4w LED (-LAS); 40,000 hour

SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

MOUNTING: FA-111-SM surface mount J-box

FINISH: Aluminum-Black texture polyester powder coat. Optional finishes available Brass-Unfinished brass. Optional finishes available.

LEDS by CREE 👄	-
- Star	SL-25-BRS

ORDERING	INFORMATION
CATALOG NO	DESCRIPTION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
SL-25-BLT	Cast Aluminum Surface Mount Bullet with Aiming Bracket and J-Box	20w MR16 FL(BAB)	2.0 lbs.
SL-25-BRS	Cast Brass Surface Mount Bullet with Aiming Bracket and J-Box	20w MR16 FL(BAB)	3.0 lbs.

LIGHT DISTRIBUTIONS AND PHOTOMETRICS





