

INSTALLATION INSTRUCTIONS

IMPORTANT NOTE:

- Surface gets hot. Allow to cool down prior to replacing LED.
- Do not look into LED when on.
- Use only with correct wattage/LED marked on fixture.
- Do not operate fixture with missing or damaged parts.

MAINTENANCE: To assure proper operation and efficiency, ensure all seals, anchor bolts and connections are properly secured. A regular scheduled service is recommended.

SAFETY WARNING: To prevent electrical shock, turn off electrical supply at circuit breaker when installing or servicing.

NOTE: Save these instructions for future reference.

INSTALLATION:

1. Turn off electrical supply at circuit breaker starting installation.
2. Remove cap by rotating counter-clockwise.
3. Mark mounting hole locations of fixture on surface to be mounted.
4. Drill pilot holes for x2 mounting screws (supplied).
5. Secure fixture to location tightly using #6 phillips screws with #2 phillips screw driver.
6. Re-install cover by rotating clockwise over threaded stud.

Note: Fixture is supplied with 55-inches of 18/2 lead wire for secure connection to the main 12v supply cable.

7. Turn on power to fixture and check for proper installation.

Note: For cleaner installation, wire thru hole can be drilled behind fixture to hide lead wires.

LED INSTALLATION / REPLACEMENT:

1. Turn off electrical supply at circuit breaker before starting installation.
2. Remove cover by rotating cap counter-clockwise.
3. Gently remove LED tape from circular bracket.
4. Peel backing off new LED tape replacement and cut to correct length.
5. Replace cap by rotating clockwise over threaded stud.
6. Turn on electrical supply at circuit breaker and check for proper installation.

Note: Do not exceed maximum wattage marked on fixture label.

