

LED MODULE DIRECTIONAL LIGHTING

PROJECT: CATALOG NUMBER:



CATALOG O	RDER LOGIC						
EXAMPLE:	DL46L	EDM15BRS					
FIXTURE							
DL	Direct	ional Light					
Series							
46							
12 VOLT LEI	D WATT	SOCKE	T KELVIN	LUMEN			
LEDM20	20w	~	2800K	1800lm			
OPTICS							
□ 15	(15°	Spot)					
□ 40 □ 60		Narrow Flood)					
□ WF		Flood) Flood, No Optic	:)				
DRIVER	•		,				
			rnal driver requi Operating range				
12v AC/DC input, Voltage Range 9v-18v Operating range: 12v-15v □ 120v input, (External universal driver—HW1260LED) Triac Dimmable Driver							
I I IZUV INDUT	(External uni	versal driver—H	W1260LED) Tria	c Dimmable Driver			
		versal driver—H loor junction bo	· · · · ·	c Dimmable Driver			
(Must use	UL listed outd		x, see page 3) W1260277LED)	c Dimmable Driver			
(Must use	UL listed outd	oor junction bo versal driver—H	x, see page 3) W1260277LED)	c Dimmable Driver			
(Must use 277v input (Must use CAP Angle Cap	UL listed outd , (External uni UL listed outd (Stand	loor junction bo versal driver—H loor junction bo dard)	x, see page 3) W1260277LED)	c Dimmable Driver			
(Must use 277v input (Must use CAP	UL listed outd , (External uni UL listed outd (Stand (Exter	loor junction bo versal driver—H loor junction bo dard) nded Cap)	x, see page 3) W1260277LED)	c Dimmable Driver			
(Must use 277v input (Must use CAP Angle Cap EC	UL listed outd , (External uni UL listed outd (Stand (Exter (Flat C	loor junction bo versal driver—H loor junction bo dard) nded Cap)	x, see page 3) W1260277LED)	c Dimmable Driver			
(Must use 277v input (Must use CAP Angle Cap EC EC FC TS	UL listed outd , (External uni UL listed outd (Stand (Exter (Flat C	loor junction bo versal driver—H loor junction bo dard) nded Cap) Cap) Shield)	x, see page 3) W1260277LED)	c Dimmable Driver			
(Must use 277v input (Must use CAP Angle Cap EC EC FC TS	UL listed outd , (External uni UL listed outd (Stanc (Exter (Flat C (Tube standard material li (Alumi	loor junction bo versal driver—H loor junction bo dard) nded Cap) Cap) Shield)	x, see page 3) W1260277LED) x, see page 3)	c Dimmable Driver			
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a	UL listed outd , (External uni UL listed outd (Stanc (Exter (Flat C (Tube standard material li (Alumi (Unfin	loor junction bo versal driver—H loor junction bo dard) nded Cap) Cap) Shield) sted) sted) inum- Black Tex ished- Brass) es (See page 4	x, see page 3) W1260277LED) x, see page 3) ture) for more color o	ptions)			
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a	UL listed outd , (External uni UL listed outd (Stanc (Exter (Flat C (Tube standard material li (Alumi (Unfin	loor junction bo versal driver—H loor junction bo dard) nded Cap) Cap) Shield) sted) sted) inum- Black Tex ished- Brass) es (See page 4	x, see page 3) W1260277LED) x, see page 3) ture) for more color o				
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a	UL listed outd , (External uni UL listed outd (Stand (Exter (Flat C (Tube standard material li (Alumi (Unfin nd Acid Finish RAL Colors (E	loor junction bo versal driver—H loor junction bo dard) nded Cap) Cap) Shield) sted) sted) inum- Black Tex ished- Brass) es (See page 4	x, see page 3) W1260277LED) x, see page 3) ture) for more color o	ptions)			
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a Pantone & MOUNTING 12v - FA03	UL listed outd , (External uni UL listed outd (Exter (Flat C (Tube standard material li (Alumi (Unfin md Acid Finish RAL Colors (E Black 9" ABS s	loor junction bo versal driver—H loor junction bo dard) nded Cap) Cap) Shield) sted) inum- Black Tex ished- Brass) es (See page 4 nter RAL or Pan stake (Included	x, see page 3) W1260277LED) x, see page 3) ture) for more color o tone number at with Aluminum	ptions) end of part number) version)			
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a Pantone & MOUNTING 12v - FA03 12v - FA03	UL listed outd , (External uni UL listed outd (Stand (Exter (Flat C (Tube standard material li (Alumi (Unfin nd Acid Finish RAL Colors (E Black 9" ABS s LG Large black	loor junction bo versal driver—H loor junction bo dard) nded Cap) Cap) Shield) sted) sted) es (See page 4 nter RAL or Panti stake (Included : 9" ABS stake, t	x, see page 3) W1260277LED) x, see page 3) ture) for more color o tone number at with Aluminum apped 1/2" NPS	ptions) end of part number) version)			
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a Pantone & MOUNTING 12v - FA03 12v - FA03 (Inclue 120-277v -	UL listed outd , (External uni UL listed outd (Stand (Exter (Flat C (Tube standard material li (Alumi (Unfin nd Acid Finish RAL Colors (E Black 9" ABS s LG Large black ded with Brass Mounting opt	loor junction bo versal driver—H loor junction bo dard) nded Cap) Shield) sted) sted) es (See page 4 nter RAL or Pan stake (Included : 9" ABS stake, t and Copper ve ions not supplie	x, see page 3) W1260277LED) x, see page 3) ture) for more color o tone number at with Aluminum apped 1/2" NPS rsions) ed. FA26, or othe	ptions) end of part number) version)			
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a Pantone & MOUNTING 12v - FA03 12v - FA03 (Inclue 120-277v -	UL listed outd , (External uni UL listed outd (Stand (Exter (Flat C (Tube standard material li (Alumi (Unfin nd Acid Finish RAL Colors (E Black 9" ABS s LG Large black ded with Brass Mounting opt	loor junction bo versal driver—H loor junction bo dard) nded Cap) Shield) sted) sted) es (See page 4 nter RAL or Pan stake (Included : 9" ABS stake, t and Copper ve ions not supplie	x, see page 3) W1260277LED) x, see page 3) ture) for more color o tone number at with Aluminum apped 1/2" NPS rsions) ed. FA26, or othe	ptions) end of part number) version) er Focus JBoxes			
(Must use 277v input (Must use CAP Angle Cap EC FC TS MATERIAL (BLT BRS Premium a Pantone & MOUNTING 12v - FA03 12v - FA03 (Inclue 120-277v -	UL listed outd , (External uni UL listed outd (Stand (Exter (Flat C (Tube standard material li (Alumi (Unfin nd Acid Finish RAL Colors (E Black 9" ABS s LG Large black ded with Brass Mounting opt	loor junction bo versal driver—H loor junction bo dard) nded Cap) Shield) sted) sted) es (See page 4 nter RAL or Pan stake (Included : 9" ABS stake, t and Copper ve ions not supplie	x, see page 3) W1260277LED) x, see page 3) ture) for more color o tone number at with Aluminum apped 1/2" NPS rsions) ed. FA26, or othe	ptions) end of part number) version) er Focus JBoxes			

TYPE:

12v option with standard cap (shown) 12v-277v and alternate cap styles available








FOCUS INDUSTRIES INC.


25301 COMMERCENTRE DRIVE LAKE FOREST, CA. 92630 949.830.1350 | TOLL FREE: 888.882.1350 WWW.FOCUSINDUSTRIES.COM











SPECIFICAT	IONS	
INTERNALS	VOLTAGE	12V-277V
	WATTAGE	20W
	LUMENS	1800lm
	WIRING	12V Black 3 foot 18/2 zip cord from base of fixture. For 25ft 16/2 fixture lead wire add (-25F) to catalog number (12V Only) 120V-277V Black 12" pigtail from driver
	DRIVER	12V AC/DC-Integrated on board 120V-277V remote driver HW1260LED (Must use FA2660W post or outdoor rated junction box)
	LENS	High impact clear tempered convex glass
	O-RING	2x - 70 Durometer 400° red silicone
	OPTICS	Interchangeable: 15° Spot, 40° Narrow Flood, 60° Wide Flood, 160° Very Wide Flood (no optics)
EXTERNALS	HOUSING	Extruded Aluminum, Brass
	HEAT SINK	Cast Aluminum, Cast Brass,
	SWIVEL	Cast Aluminum, Cast Brass, (240° rotation)
	CAP	Matching Aluminum, Brass
	MOUNT	12V: FA03 Black ABS 9" Stake - Aluminum version (standard); FA03LG Large Black ABS 9" Stake 120V-277V: Mounting options not supplied. Order separately FAJBox or other outdoor rated mount (More available. See page 3
	FINISH	Aluminum: Polyester textured powder coat (More options available. See page 4) Brass: Acid finishes (More options available. See page 4.)
	LISTINGS	IP66. Indoor/Outdoor use. Suitable for wet locations




FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA. 92630 949.830.1350 | TOLL FREE: 888.882.1350 WWW.FOCUSINDUSTRIES.COM

DESIGNED MANUFACTURED IN THE USA



THIS DOCUMENT CONTAINS INFORMATION PROPRIETY OF FOCUS INDUSTRIES, AND ITS POSSESSION DOES NOT GRANT ANY RIGHTS TO REPRODUCE, MANUFACTURE, SELL, OR DISCLOSE THE CONTENTS DESCRIBED IN THIS DOCUMENT. REPRODUCTION, DISCLOSURE, AND MANUFACTURING WITHOUT THE WRITTEN CONSENT AND AUTHORIZATION OF FOCUS INDUSTRIES IS STRICTLY FORBIDDEN.







FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA. 92630 949.830.1350 | TOLL FREE: 888.882.1350 WWW.FOCUSINDUSTRIES.COM






THIS DOCUMENT CONTAINS INFORMATION PROPRIETY OF FOCUS INDUSTRIES, AND ITS POSSESSION DOES NOT GRANT ANY RIGHTS TO REPRODUCE, MANUFACTURE, SELL, OR DISCLOSE THE CONTENTS DESCRIBED IN THIS DOCUMENT. REPRODUCTION, DISCLOSURE, AND MANUFACTURING WITHOUT THE WRITTEN CONSENT AND AUTHORIZATION OF FOCUS INDUSTRIES IS STRICTLY FORBIDDEN.



LED MODULE DIRECTIONAL LIGHTINGDL46LEDMPROJECT:TYPE:DATE:

CATALOG NUMBER:



Images enhanced to illustrate usage of mounting options. Drawings not to scale. (see page 2 for product dimensions)





FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA. 92630 949.830.1350 | TOLL FREE: 888.882.1350 WWW.FOCUSINDUSTRIES.COM





THIS DOCUMENT CONTAINS INFORMATION PROPRIETY OF FOCUS INDUSTRIES, AND ITS POSSESSION DOES NOT GRANT ANY RIGHTS TO REPRODUCE, MANUFACTURE, SELL, OR DISCLOSE THE CONTENTS DESCRIBED IN THIS DOCUMENT. REPRODUCTION, DISCLOSURE, AND MANUFACTURING WITHOUT THE WRITTEN CONSENT AND AUTHORIZATION OF FOCUS INDUSTRIES IS STRICTLY FORBIDDEN. LED MODULE DIRECTIONAL LIGHTING

CATALOG NUMBER:

12V 20W LED MODULE

L#	ССТ	CRI	WATTS	LUMENS	RATED HOURS
LEDM20	2800K	80	20	1800	50,000

FINISHES

RAL #:

PANTONE #:

Need help finding a RAL color? https://www.ralcolor.com/

Need help finding a Pantone color?

https://www.pantone.com/color-finder


NDUSTRIES

 ${\sf landscape} \bullet {\sf architectural} \bullet {\sf hospitality} \bullet {\sf entertainment} \bullet {\it illumination}$

STANDARD FINISHES



PREMIUM FINISHES







TYPE: